



Technical data: Pantera 4503

Model	Pantera 4503	Pantera 4503-W	Pantera 4503-H
Nominal volume (l)	4,500		
Actual volume (l)	4,800		
Fresh water rinse tank (l)	500		
Working width (m)	21 – 40		
Fuel tank capacity (l)	230		
DEF tank (l)	20		
Max. working speed (km/h)	20		
Transport speed (km/h)	up to 50		
Length (m) (Transport position, plus external wash down kit)	8.60		
Transport width (mm)	2.55	2.75	2.55
Spraying height min./max. (m)	0.50 – 2.50 with lift module 0.50 – 3.20		0.50 – 3.00 with lift module 0.50 – 3.70
No. of part-width sections (min./max.)	7 – 13		
No. of sections with individual nozzle switching: Amaswitch or AmaSelect	up to 80		
Unladen weight (kg)	9,600	9,950	10,500
Max. total weight (kg)	15.800 (depending on tyres)		
Delivery capacity pump (l/min)	520		
Turning circle, all-wheel steer (m)	4.50		
Track width (mm)	1.80 – 2.40	2.25 – 3.00	1.80 – 2.40 at 1.25 2.10 – 2.60 at 1.70
Ground clearance (m)	1.20	1.20	1.25 / 1.70 in the lower/upper working position
Engine power	max. 160 kW (218 HP) (Data according to ISO TR 14396)		

Illustrations, content and technical data are not binding! Deviations of technical data are possible depending on the equipment. The illustrations may deviate from the requirements for local road traffic regulations.