

Technical data

ZA-M	1001 Special	1201	1501
Working width (m)	10–36		
Hopper volume (l)	1,000	1,200	1,500
– with hopper extension 1 x S 500 (l)	1,500	1,700	2,000
– with hopper extension 2 x S 500 (l)	–	2,200	2,500
– with hopper extension 3 x S 500 (l)	–	2,700	3,000
– with hopper extension 1 x L 1000 (l)	–	2,200	2,500
– with hopper extension S 500 + L 1000 (l)	–	2,700	3,000
Payload (kg)	1,800	3,100	3,100
Filling height (m)	1.07	1.07	1.14
– with hopper extension 1 x S 500 (m)	1.21	1.21	1.28
– with hopper extension 2 x S 500 (m)	–	1.35	1.42
– with hopper extension 3 x S 500 (m)	–	1.49	1.56
– with hopper extension 1 x L 1000 (m)	–	1.35	1.42
– with hopper extension S 500 + L 1000 (m)	–	1.49	1.56
Filling width (m)	2.15	2.15	2.15
– with hopper extension 1 x S 500 (m)	2.16	2.16	2.16
– with hopper extension 1 x L 1000 (m)	–	2.76	2.76
Total width (m)	2.44	2.44	2.44
– with hopper extension 1 x L 1000 (m)	–	2.93	2.93
Total length (m)	1.42	1.42	1.42
Spreading disc speed (U/min)	720 (Standard speed)		
Weight base machine (kg) (Extensions S 500 + 27 kg / L 1000 + 57 kg)	309	319	332

Illustrations, content and technical data are not binding! Deviations of technical data are possible depending on the equipment. The illustrations may deviate from the requirements for local road traffic regulations.

Ahead in the field and safe on the road: ZA-M

ZA – the spreader



AMAZONEN-WERKE H. Dreyer GmbH & Co. KG
 P. O. Box 51 · D-49202 Hasbergen-Gaste/Germany
 Phone: +49 (0)5405 501-0 · Fax: +49 (0)5405 501-193