

Technical data

Cenius mounted cultivator		Cenius 3003 Special/Super	Cenius 3503 Special/Super	Cenius 4003 Special/Super	Cenius 4003-2 Special/Super
Working width (m)		3.00	3.50	4.00	4.00
Execution		Rigid	Rigid	Rigid	Hydraulic folding
Transport width (m)		3.00	3.50	4.00	3.00
Transport length with road lights (m)		3.80	3.80	3.80	3.80
Transport height (m)		–	–	–	–
Weight – base machine (kg) simplest execution ³	Special	1,482	1,617	1,761	2,415
	Super	2,024	2,209	2,402	3,065
Linkage		3-point linkage mounted (Cat. III)			
Number of tines		11	12	13	13
Tine execution	Special	C-Mix Special tines with shear bolt overload safety device			
	Super	C-Mix Super tines with pressure spring overload safety device			
Number of tine rows		3			
Tine spacing in the row (mm)		810	870	855	855
Tine spacing (mm)		273	291	286	286
Frame height (mm)		800			
Working depth (cm)		5–30			
Maximum operational speed (km/h)		8–15			
Power requirement from (kW/HP)		90/125	105/140	120/160	120/160
No. of d/a tractor spool valves		0, 1 ¹ , 2 ²	0, 1 ¹ , 2 ²	0, 1 ¹ , 2 ²	1, 2 ¹ , 3 ²

Cenius-2TX trailed cultivator		Cenius 4003-2TX Special/Super	Cenius 5003-2TX Special/Super	Cenius 6003-2TX Special/Super	Cenius 7003-2TX Special/Super	Cenius 8003-2TX Special/Super
Working width (m)		4.00	5.00	6.00	7.00	8.00
Operational speed (km/h)		8–15				
Working depth (cm)		5–30				
No. of tines		13	17	21	25	29
Tine execution	Special	C-Mix Special tines with shear bolt overload safety device				
	Super	C-Mix Super tines with pressure spring overload safety device				
Tine spacing (mm)		307	294	286	280	280
Power requirement from/to (HP/m)		50–80				
Transport length (m)		9.30–10.10				
Transport width (m)		3.00				
Transport height (m)		2.80	3.10	3.70	4.00	4.60
Weight – base machine (kg) simplest execution ³	Special	4,199	4,678	5,719	6,051	5,640
	Super	4,830	5,513	6,754	7,286	8,073
Permitted support load (kg)		1,550				
Number of tine rows		4				
Frame height (mm)		800				
No. of d/a tractor spool valves		2, 3 ¹ , 4 ²				

¹with hydraulic depth adjustment ²with hydraulic adjustment of the levelling unit

³with mechanical depth setting, traffic lights, set C-Mix Special tines, 80 mm C-Mix share tip and guide plate, set of spring closers, SW 520

Illustrations, content and technical data are not binding! Technical data may deviate according to the level of equipment.

Machine illustrations can vary due to country-specific traffic legislation.