



KG 3001 rotary cultivator

KE rotary harrows and KX/KG rotary cultivators

| Model | Working width (m) | Transport width (m) | Power requirement from (kW/HP) | For tractor output up to (kW/HP) | Number of tine carriers | Basic weight without roller (kg) | Basic weight with roller KWM 580 from (kg) |
|-----------------|-------------------|---------------------|--------------------------------|----------------------------------|-------------------------|----------------------------------|--|
| KE 2501 Special | 2,50 | 2,50 | 40/55 | 102/140 | 8 | 995 | - ¹ |
| KE 3001 Special | 3.00 | 3.00 | 48/65 | 102/140 | 10 | 1,060 | 1,679 |
| KE 3001 Super | 3.00 | 3.00 | 59/80 | 135/180 | 10 | 1,120 | 1,739 |
| KE 3501 Super | 3.50 | 3.50 | 63/85 | 135/180 | 12 | 1,120 | 1,799 |
| KE 4001 Super | 4.00 | 4.03 | 66/90 | 135/180 | 14 | 1,330 | 1,949 |
| KX 3001 | 3.00 | 3.00 | 66/90 | 142/190 | 10 | 1,350 | 1,969 |
| KG 3001 Special | 3.00 | 3.00 | 66/90 | 161/220 | 10 | 1,340 | 1,959 |
| KG 3501 Special | 3.50 | 3.50 | 77/105 | 161/220 | 12 | 1,450 | 2,029 |
| KG 4001 Special | 4.00 | 4.03 | 88/120 | 161/220 | 14 | 1,580 | 2,199 |
| KG 3001 Super | 3.00 | 3.00 | 66/90 | 220/300 | 10 | 1,360 | 1,979 |
| KG 3501 Super | 3.50 | 3.50 | 77/105 | 220/300 | 12 | 1,480 | 2,059 |
| KG 4001 Super | 4.00 | 4.12 | 88/120 | 220/300 | 14 | 1,610 | 2,229 |

¹Only available with PW tooth packer roller

Following rollers

| Model | Cage roller | | Tooth packer roller | | | | | | Trapezium ring roller | | | | | | Wedge ring roller | | | | KWM 600 wedge ring roller with Matrix tyre profile | | | |
|--------------------------|-------------|--------|---------------------|--------|--------|--------|--------|---------|-----------------------|---------|---------|---------|---------|---------|-------------------|--------|--------|--------|--|------|------|-----|
| | PW 520 | PW 580 | PW 500 | PW 550 | PW 600 | PW 650 | PW 700 | TRW 500 | TRW 550 | TRW 600 | TRW 650 | TRW 700 | TRW 750 | TRW 800 | KW 520* | KW 580 | KW 630 | KW 680 | 3.00 | 3.50 | 4.00 | |
| Working width (m) | 3.00 | 4.00 | 2,50 | 3.00 | 4.00 | 3.00 | 3.50 | 4.00 | 3.00 | 3.50 | 4.00 | 3.00 | 3.50 | 4.00 | 3.00 | 3.00 | 3.50 | 4.00 | 3.00 | 3.50 | 4.00 | |
| Diameter (mm) | 520 | | 500 | | | 600 | | | 500 | | | 600 | | | 520 | 580 | | | 600 | | | |
| Basic weight from (kg) | | | | | | | | | | | | | | | | | | | | | | |
| with 12.5 cm row spacing | - | - | - | - | - | - | - | - | 534 | 612 | - | 638 | 733 | 828 | 339 | 521 | 593 | 668 | 529 | 606 | 669 | |
| with 14.6 cm row spacing | - | - | - | - | - | - | - | - | - | 572 | - | - | 692 | - | - | - | 567 | - | - | 578 | - | |
| with 15.0 cm row spacing | 280 | 359 | 327 | 385 | 500 | 521 | 598 | 675 | 494 | - | - | 592 | - | - | - | 481 | - | - | 500 | - | - | |
| with 15.4 cm row spacing | - | - | - | - | - | - | - | - | - | - | - | - | - | - | 759 | - | - | - | 603 | - | - | 638 |

*only for row spacings of 12.5 cm and a working width of 3 m

Illustrations, content and technical data are not binding! Technical data may deviate according to the level of equipment. Machine illustrations can vary due to country-specific traffic legislation.