

<b>Catros<sup>XL</sup> mounted compact disc harrows</b>	<b>Mounted models, rigid</b>		
	<b>Catros<sup>XL</sup> 3003</b>	<b>Catros<sup>XL</sup> 3503</b>	<b>Catros<sup>XL</sup> 4003</b>
Working width (m)	3.00	3.50	4.00
Operational speed (km/h)	12 – 18		
Power requirement from (kW/HP)	88/120	103/140	118/160
Diameter discs/thickness (mm) Catros <sup>XL</sup> (fine serrated or coarse serrated)	610/6		
Disc spacing (mm)	250		
Number of discs	2 x 12	2 x 14	2 x 16
Working depth (cm)	Catros <sup>XL</sup> 5 – 16		
Transport length with road lights (m)	3,340		
Transport width (m)	3.00	3.50	4.00
Transport height (m)	1.50		
Weight without roller (kg)	1,470	1,710	1,940
Weight (kg) Catros <sup>XL</sup> (base machine, mechanical depth adjustment, wedge ring roller)	1,960	2,270	2,580
Number of double-acting spool valves (with hydraulic depth control)	– (1)	– (1)	– (1)

<b>Certos-2TX trailed heavy compact disc harrows</b>	<b>Certos 4001-2TX</b>	<b>Certos 5001-2TX</b>	<b>Certos 6001-2TX</b>	<b>Certos 7001-2TX</b>
Execution	folding/trailed	folding/trailed	folding/trailed	folding/trailed
Working width (m)	4.00	4.90	6.00	7.00
Operational speed (km/h)	10 – 15			
Transport speed (km/h)	40			
Diameter discs/thickness (mm) Certos (serrated)	660/6			
Number of discs	24	28	36	40
Disc spacing (mm)	350			
Working depth (cm)	7 – 20			
Power requirement from/to (HP/m)	160 – 230	200 – 300	250 – 400	> 350
Transport length (m)	8.04	8.04	8.14	8.14
Transport width (m)	2.85			
Transport height (m)	2.96	3.34	3.85	3.99
Total weight (kg) (base machine + KW wedge ring roller 580 mm)	6,550	7,100	8,200	8,700
Actual support load (kg)	1,500	1,500	1,700	1,700

Illustrations, content and technical data are not binding! Technical data may deviate according to the level of equipment. Machine illustrations can vary due to country-specific traffic legislation.