

Technical data

ZA-TS	ZA-TS Super Profis Tronic	ZA-TS Ultra Profis Tronic	ZA-TS Super Profis Hydro	ZA-TS Ultra Profis Hydro
Working width	15–36 m	15–54 m	15–36 m	15–54 m
Hopper capacity with S 1700 extension	1,700 l			
Hopper capacity with S 2000 extension	2,000 l			
Hopper capacity with L 2200 extension	2,200 l			
Hopper capacity with L 2700 extension	2,700 l			
Hopper capacity with L 3200 extension	3,200 l			
Hopper capacity with L 4200 extension	–	4,200 l	–	4,200 l
Payload	3,200 kg	4,500 kg	3,200 kg	4,500 kg
Filling height with S 1700 extension	1.23 m			
Filling height with S 2000 extension	1.32 m			
Filling height with L 2200 extension	1.31 m			
Filling height with L 2700 extension	1.42 m			
Filling height with L 3200 extension	1.54 m			
Filling height with L 4200 extension	–	1.77 m	–	1.77 m
Filling width with S extension	2.22 m			
Filling width with L extension	2.71 m			
Total width with S extension	2.58 m			
Total width with L extension	2.92 m			
Drive	540 U/min		hydraulic	
Lower linkage	Category II	Category III	Category II	Category III
Weighing system	Weighing system as standard			
Regulating electronics	ISOBUS communication via AMATRON 3, CCI 100, AMAPAD or other non-Amazone ISOBUS terminals			
Tractor valves required	Not necessary, (1 d/a valve for hyd. rollover cover)		1 d/a valve or load sensing for drive (oil capacity min. 70 l/min). (1 d/a valve for hyd. rollover cover)	
ZG-TS	5500		8200	
Working width	15–54 m			
Hopper capacity	5,500 l		8,200 l	
Permissible total weight	max. 12,000 kg		max. 12,000 kg	
Payload on public roads	max. 10,000 kg		max. 9,800 kg	
Filling width	3.45 m			
Total length	6.60 m			
Height	2.26 m–3.10 m (depending on the tyres fitted)			
Width	2.26 m–2.75 m (depending on the tyres fitted)			
Drive	ZG-TS: 540 R.P.M.; ZG-TS Hydro: hydraulic spreading disc drive			

Illustrations, descriptions and technical data are not binding and subject to change! Machine illustrations can vary due to country-specific traffic legislation.



AMAZONEN-WERKE H. DREYER GmbH & Co. KG

P. O. Box 51 · D-49202 Hasbergen-Gaste

Phone: +49 (0)5405 501-0 · Telefax: +49 (0)5405 501-193