

Technical data UX Special, UX Super and UX 11200

Model	UX 3200 Special	UX 3200 Super	UX 4200 Special	UX 4200 Super	UX 5200 Super	UX 6200 Super	UX 11200
Actual volume (l)	3,600	3,600	4,600	4,600	5,600	6,560	12,000
Fresh water rinse tank (l)	320	320	550	550	550	550	900
Working width (m)	15–30	18–36	15–30	18–40	18–40	18–40	24–40
Height (m)	Super-S boom: 3.22 / Super-L boom: 3.35						3.90
Transport length (m)	6.25		6.80				9.70
Transport width (m)	Super-S boom: 2.40 three-fold Super-L boom: 2.40 / four-fold Super-L boom: 2.60						2.85
Empty weight (kg)	2,908–3,344	3,032–3,722	2,998–3,434	3,069–3,728	3,221–3,880	3,651–4,310	7,870–8,284
Pump equipment (l/min)	260/380	420	260/380	420/520	520	520	750
Max. suction capacity (l/min)	400/500	600	400/500	600/700	700	700	900
Ground clearance	0.78 m (with tyres Ø 1835 mm)						
Spraying height	0.5–2.5 m (with tyres Ø 1835 mm)						
Operational pressure, max. (bar)	< 10						

Illustrations, content and technical data are not binding! The illustrations may deviate from the requirements for local road traffic regulations.



The small self-propelled machine! UF in combination with front tank FT 1001

Specially for large volume mounted sprayers, the use of a front tank is the obvious solution.

On hilly terrain and in small fields the manoeuvrability is excellent.

The Flow-Control electronics provide an automatic, tank level dependent circulation and emptying.



AMAZONEN-WERKE H. DREYER GmbH & Co. KG

P. O. Box 51 · D-49202 Hasbergen-Gaste/Germany

Phone: +49 (0)5405 501-0 · Fax: +49 (0)5405 501-193